

SRAC-23 AC-Powered Indoor Siren Series

Uninterrupted Power Uncompromising Protection



- AC-Powered Indoor Siren & Doorbell chime
- Rechargeable battery backup (SRAC-23B only)
- Entry and exit delay beeps

SRAC-23 Series is multifunctional AC-powered indoor siren and doorbell chime. SRAC-23 Series introduces AC-powered indoor sirens that plug into any standard power outlets for quick and simple installation. This series employs reliable power supply to ensure the sirens deliver uncompromising protection at all times and blare alarm sounds when intrusions occur. The model SRAC-23B provides rechargeable battery backup.

This multipurpose siren series can be further configured to emit entry/exit delay beeps. If your control panel is distant from the front door and you have difficulty hearing its entry/exit delay beeps, SRAC-23 Series can serve as a useful reminder device, emitting entry/exit delay beeps that urge you to disarm your security system or leave quickly. Selectable volume levels are designed for the sirens' entry/exit delay beeps.

Features

- Multifunctional AC-Powered indoor siren and doorbell chime
- Plugs into any standard power outlet for quick and simple installation
- Rechargeable battery backup (SRAC-23B only)
- Emit door chime, alarm sound or entry/exit delay beeps
- Siren audible performance for burglar/panic alarm and fire/water alarm
- Three selectable volume levels for entry and exit delay beeps
- Transmits AC power failure, low battery and supervisory signals
- Indication beeping sound adjustment
- Pervious alarm warning
- LED as an indicator of system status
- Completely wire-free

Specifications

SRAC-23-F1

Frequency	868 MHz / 433 MHz
Power Input	100-240VAC
Siren Output	95 dB at 1 meter
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	95 mm x 63 mm x 83 mm

SRAC-23 AC-Powered Indoor Siren Series

SRAC-23B-F1

Frequency	868 MHz / 433 MHz
Power Input	100-240VAC
Backup Battery	Ni-MH AAA Battery x 4
Backup Battery Life	50 days
Siren Output	95 dB at 1 meter
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	95 mm x 63 mm x 83 mm

* Note: Battery life may vary by configuration mode, usage, and environment.

Ordering Information

SRAC-23-F1	Multifunctional AC-Powered indoor siren and doorbell chime
SRAC-23B-F1	Multifunctional AC-Powered indoor siren and doorbell chime with backup battery