



# Monitor Audio Subwoofer

## Monitor Audio Radius 380 subwoofer

Radius 380 er en kompakt men meget kraftfull subwoofer med 2 stk 8" basser. Den spesielle løsningen med aktiv bassradiator (ABR) og en klasse-D forsterker på 200 watt gir hurtighet som gjør at den matcher alle kvalitetshøytalere. Radius er Monitor Audio sin kompakte designserie. Teknisk design og deler lånes fra Bronze-serien og er dermed i høyeste kvalitet og langt over hva som forventes av designmodeller. Rålekker finish i sort, hvit eller valnøttbhøylanslakk passer inn overalt og lyden er i absolutt toppklasse. Radius har vunnet utallige tester over hele verden.



## SPECIFICATIONS

System Format Active sub-woofer Auxiliary (ABR) loading. 18mm MDF cabinet system

Low Frequency Limit	30Hz (- 6dB)
Upper Frequency Limit Variable	40 - 120 Hz @ 24dB/Octave
Amplifier Power Output	200 Watts @ 1% THD+N
Amplifier Classification	Class D amplifier with Switch mode power supply (SMPSU)
Bass EQ Switch	Music / Movie / Impact
Phase Control	0 & 180 degrees
Auto Sensing Line Level	>3.5mV
Input Level Requirements	Standby after approximately 15 minutes if no signal sensed
Driver Compliment	1 x 8" (200mm) C-CAM® long throw driver 1 x 8" (200mm) Auxiliary bass radiator
Dimensions including amp & feet	(HxWxD) 308 x 290 x 305mm
Connections Stereo	RCA in, LFE in, 12v Trigger in (3.5mm mono mini-jack) 12v Trigger Input 5 - 12v via 3.5mm mono mini-jack socket
Power Consumption	200 Watts / 0.5 Watts in Standby (ErP approved)
Weight	(Unpacked) 10.16Kg