

Innfelthøytaler Tak/vegg

UTENDØRS STEREO HØYTTALER INNFELT TAK - SAWC-280T2

Innfelthøttaler i vegg / tak. For å kunne levere stereo lyd med høy ytelse. Perfekt for forhold hvor plass tilgjengelig er begrenset.

SPECIFICATIONST

Frequency Response	50 Hz — 30 kHz
Maximum SPL	109 dBA
Drivers	8" C-CAM cone bass driver 2 x 1" C-CAM Gold Dome tweeters (fixed angle)
Overall Diameter (Including Grille)	285 mm (111/4")
Mounting Depth	97.55 mm (37/8")
Construction Material	Mineral Filled PC-ABS Polymer (UL V0 Fire Retardant, RoHS2 Compliant)
Operating Temperature Range	-34° to 79° C -29° to 174° F
Sensitivity (1W@1M)	88 dB (both channels driven)
Power Handling (RMS)	100 W
Adjustment Controls	HF Level Switch (+3 dB / 0 dB / -3 dB) - Adjustable at the point of installation
Overall Depth (Including Grille)	102.5 mm (41/32")
Optional Square Grille - Outer Dimensions	285 x 285 mm (111/4")
Grille	S5430 Stainless Steel
Weight	2.8 kg (6 lb 2 oz)
Nominal Impedance	8 + 8 ohms
Recommended Amplifier Requirements	20 — 100 W
Connection	2 x (2 pairs) Gold plated push style terminal
Cut-Out Hole Diameter	247 mm (93/4")
Fixing Type	3 position Tri-Grip dog leg fixings
Magnets	Samarium Cobalt