


Controlled Performance


In-Wall Centres

CP-WT140LCR



Sensitivity (1W@1m)	88 dB
Cut Out Dimensions (H x W)	7 ^{3/16} " x 11 ^{3/4} " / 183 x 299 mm
Mounting Depth	3 ^{13/16} " / 97 mm
Power Handling (RMS)	100 W
Impedance	6 ohms
Driver Size & Technology	2 x 4" MMP II drivers 1" C-CAM pivoting Gold Dome tweeter HF level switch
Pre-Construction Bracket	WB4LCR (Dark brown)


CP-WT240LCR



Sensitivity (1W@1m)	88 dB
Cut Out Dimensions (H x W)	7 ^{3/16} " x 11 ^{3/4} " / 183 x 299 mm
Mounting Depth	3 ^{13/16} " / 97 mm
Power Handling (RMS)	100 W
Impedance	6 ohms
Driver Size & Technology	2 x 4" C-CAM drivers 1" C-CAM pivoting Gold Dome tweeter HF level switch Boundary compensation switch
Pre-Construction Bracket	WB4LCR (Dark brown)

Performance Full Size

CP-IW260X



Sensitivity (1W@1m)	89 dB
Cut Out Dimensions (H x W)	34 ^{21/32} " x 9" / 880 x 230 mm
Mounting Depth	3 ^{3/4} " / 96 mm
Power Handling (RMS)	150 W
Impedance	6 ohms
Driver Size & Technology	2 x 6 ^{1/2} " C-CAM bass drivers 2 x 4" C-CAM mid-range drivers 1" C-CAM Gold Dome tweeter HF & MF level switches Boundary compensation switch Vertical or horizontal orientation
Pre-Construction Bracket	WB12 (Green)

