


Super Slim

Our innovative Super Slim speakers back box design delivers full frequency performance with wide installation versatility. Ideal for standard stud walls and where depth is very restricted. The Super Slim In-Wall products are designed for both vertical or horizontal installation.

In-Ceiling

CSS230



Closed back Opened back



Sensitivity (1W@1m)	86 dB
Cut Out Diameter	8 ¹ / ₄ " / 211 mm
Mounting Depth	2" / 50 mm
Power Handling (RMS)	40 W – Full range 60 W – With crossover set to 100 Hz @ 12 dB/Octave
Impedance	8 ohms
Driver Size & Technology	3 x 3" C-CAM drivers, enabling slim profile with the performance of a single 6" driver ³ / ₄ " C-CAM pivoting Gold Dome tweeter Sealed rear enclosure for acoustic isolation back box Rubber plug can be removed for open back design and increased low frequency performance
Pre-Construction Bracket	CB6 (Purple)

In-Wall

AVAILABLE
December 2017

WSS130




2"
50 mm



WSS230



2"
50 mm



WSS430



2"
50 mm



Sensitivity (1W@1m)	87 dB	87 dB	87 dB
Cut Out Dimensions (H x W)	13 ¹ / ₂ x 4" / 346 x 101 mm	13 ¹ / ₂ x 4" / 346 x 101 mm	13 ¹ / ₂ x 4" / 346 x 101 mm
Mounting Depth	2" / 50 mm	2" / 50 mm	2" / 50 mm
Power Handling (RMS)	60 W – Full range 100 W – With crossover set to 100Hz@12dB/Octave	60 W – Full range 100 W – With crossover set to 100Hz@12dB/Octave	75 W – Full range 120 W – With crossover set to 100Hz@12dB/Octave
Impedance	8 ohms	8 ohms	8 ohms
Driver Size & Technology	3 x 3" MMP II drivers, enabling slim profile with the performance of a single 6" driver 1" C-CAM pivoting Gold Dome tweeter	3 x 3" C-CAM drivers, enabling slim profile with the performance of a single 6" driver 1" C-CAM pivoting Gold Dome tweeter	3 x 3" C-CAM drivers, enabling slim profile with the performance of a single 6" driver MPD high frequency transducer – rotatable for vertical or horizontal installation
Pre-Construction Bracket	WB3 (Dark blue)	WB3 (Dark blue)	WB3 (Dark blue)

WSS430

The WSS430 uses concepts and materials taken directly from our flagship Platinum II speakers. Almost every component is unique to this model, created to deliver the most critical of audiophile and cinema experiences with superlative ease. The WSS430 MPD high frequency transducer is designed to rotate 90° to suit the chosen speaker installation.

